

RV TECHNICAL BULLETIN

DECEMBER 7,2000 BULLETIN NO. CN105

TO: RV Manufacture Paint Shop RV Paint Shops

Paint Procedure For The Dometic Corp. Plastic Refer Cap

APPLIED VEHICLES: All Model RV'S that require the Dometic Corporation roof mount plastic refrigerator vent cap and base to be painted using Sherwin Williams Automotive Paint.

ISSUE

Procedure for painting Polypropylene roof mount refrigerator Vent

ACTION

- 1. Identify the part by looking on the back to be sure it is a Dometic Refer cap. If the part cannot be identified, burning of a small sliver may be used to determine if the part is PP. If the part burns relatively clean, it should be PP.
- 2. Wash the part if necessary using Sherwin Williams cleaner W4-K157 then dry throughly.
- 3. Sanding is not required unless necessary to remove imperfections using 320 grit or finer sandpaper.
- 4. Apply two medium coats of Sherwin Williams plastic primer UPO7226. Allow UPO7226 15-20 to flash before applying Sherwin Williams Ultra 7000 Base-Coat / Clear-Coat

NOTE: FOR MORE INFORMATION ON UPO7226 REFER SHERWIN WILLIAMS PRODUCT DATA SHEET #2159

FOR TECHNICAL ASSISTANCE OR QUESTIONS CALL SHERWIN WILLIAMS RV TECHNICAL SUPPORT

Chris Nicholson Senior Technical Representative (219) 361-6605
Will Brunett RV Technical Representative (219) 361-6603
Michael Perry RV Accounts Executive (219) 361-6604