



**SHERWIN  
Williams**

INTERNATIONAL VEHICLE DIVISION  
P.O. BOX 100000, CINCINNATI, OH 45210

# ***RV TECHNICAL BULLETIN***

March 13 2001 BULLETIN NO. CN107

TO: RV Manufacture Paint Shop  
RV Paint Shops

*A/C Shroud*

Paint Procedure For The Dometic Corp. ~~Plastic Refer Cap~~

**APPLIED VEHICLES :** All Model RV'S that require the Dometic Corporation roof mount plastic refrigerator vent to be painted using Sherwin Williams Automotive Paint.

## **ISSUE**

Procedure for painting Acrylonitrile/Butadiene/Styrene (ABS) roof mount ~~refrigerator Vent~~

*SHROUD*

## **ACTION**

*A/C SHROUD*

1. Identify the part by looking on the back to be sure it is a ~~Dometic Refer cap~~. If the part cannot be identified, burning of a small sliver may be used to determine if the part is ABS. If the part emits black smoke, it should be ABS.
2. Wash the part using Sherwin Williams cleaner R7K158 then dry thoroughly.
3. Sanding is not required unless necessary to remove imperfections using 320 grit or finer sandpaper.
4. Apply one medium wet coat of Sherwin Williams P1C 62 Q-Seal. Allow 15-20 to flash before applying Sherwin Williams Ultra 7000 Base-Coat / Clear-Coat

**NOTE: FOR MORE INFORMATION ON P1C62 REFER SHERWIN WILLIAMS  
PRODUCT DATA SHEET #1095**

**FOR TECHNICAL ASSISTANCE OR QUESTIONS CALL SHERWIN WILLIAMS  
RV TECHNICAL SUPPORT**

Chris Nicholson	Senior Technical Representative	(219) 361-6605
Will Brunett	RV Technical Representative	(219) 361-6603
Michael Perry	RV Accounts Executive	(219) 361-6604