



# HOT PRODUCTS COOKTOP

## EN Manifold Bolt Replacement

### Service Kit Instructions

#### USA & CANADA

Service Office  
Dometic Corporation  
5155 Verdant Drive  
Elkhart, IN 46514

#### Service Center & Dealer Locations

Visit: [www.dometic.com/support](http://www.dometic.com/support)


Cooktop Models	Service Kit Number
R31	57725
S31	

Kit Contents	Description
57722	Threadlocker bolts (qty. 4)
50467	Range and Slide-In Installation and Operation Manual

## 1 Explanation of Symbols and Safety Instructions

This manual has safety information and instructions to help you eliminate or reduce the risk of accidents and injuries.

### 1.1 Recognize Safety Information

 **This is the safety alert symbol.** It is used to alert you to potential physical injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.

### 1.2 Understand Signal Words

A signal word will identify safety messages and property damage messages, and it will indicate the degree or level of hazard seriousness.

#### **WARNING**

This indicates a hazardous situation that, if **not** avoided, could result in death or serious injury.

**NOTICE:** Used to address practices **not** related to physical injury.

## 2 Recommended Tool List

Dometic Corporation recommends that the following tools be used while replacing the manifold bolts.


Recommended Tools and Materials	
Square Bit Driver	5/16 in. Socket Wrench
Torque Wrench	ATEQ Leak Tester

## 3 Replacement

#### **WARNING: FIRE AND/OR EXPLOSION HAZARD.**

Turn off the gas supply before replacing. Failure to obey this warning could result in death or serious injury.

This section describes how to remove the cooktop to access and replace the factory-installed manifold bolts with bolts that contain a thread locking agent.

 The images used in this document are for reference purposes only. Components and locations may vary according to specific cooktop models.

